

# DRY CHEMICAL POWDER

(Dry Chemical Powder PC ABC 90% UL)



	PORTABLE							TROLLEY			BIG WHEELED		Ve-Ex (Vehicle Extinguisher)
Model	P 100 ABC 90	P 200 ABC 90	P 300 ABC 90	P 450 ABC 90	P 600 ABC 90	P 900 ABC 90	P 1200 ABC 90	P 2500 ABC 90	P 5000 ABC 90	P 6800 ABC 90	P 13600 ABC 90	P 16000 ABC 90	P 100 SA
Type	STORED PRESSURE N2 (NITROGEN)							STORED PRESSURE N2 (NITROGEN)			STORED PRESSURE N2 (NITROGEN)		STORED PRESSURE N2 (NITROGEN)
Kapasitas	1 kg	2 kg	3 kg	4.5 kg	6 kg	9 kg	12 kg	25 kg	50 kg	68 kg	136 kg	160 kg	1 kg
Kelas Kebakaran	A, B, C							A, B, C			A, B, C		A, B, C
Tabung Silinder	TANPA LAS							DENGAN LAS			DENGAN LAS		TANPA LAS
Jarak Semprot (meter)	2 s/d 7	2 s/d 8	2 s/d 9	3 s/d 11	3 s/d 12	4 s/d 12	4 s/d 12	4 s/d 14	4 s/d 14	4 s/d 14	4 s/d 14	4 s/d 14	2 s/d 7
Waktu Semprot (detik)	9	10	11	13	16	20	25	30	50	60	1280	240	9
Tinggi (mm)	300	374	460	455	540	575	665	1050	1205	1205	1100	1400	299
Lebar (mm)	130	145	280	285	310	320	340	570	570	570	580	1100	117
Diameter Tabung (mm)	90	130	130	160	160	190	190	370	370	370	580	580	90
Temperature (°C)	-20 s/d 60							-20 s/d 60			-20 s/d 60		20 s/d 60
Tekanan Dalam Tabung	15 bar							15 bar			15 bar		15 bar
Berat Total (kg)	2.1	3.9	5.5	7.4	9.4	13.2	16.6	72	102	120	275	320	2
Fire Rating	2A.10B	3A.20B	4A.30B	6A.40B	7A.60B	12A.80B	12A.80B	20A.80B	30A.125B	30A.125B			2A.10B
Labeling	SCREEN PRINTING							STICKER			STICKER		SCREEN PRINTING
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING							COLOR:RED, UV RESISTANCE POWDER COATING			COLOR:RED, UV RESISTANCE POWDER COATING		COLOR:RED, UV RESISTANCE POWDER COATING

Tersedia juga : Purple K (BC), D-Met (Metal), Marine (Off Shore).

# FOAM

(Foam AFFF 6%)



	PORTABLE		TROLLEY		
Model	F 600 AF3	F 900 AF3	F 3000 AF3	F 5000 AF3	F 9000 AF3
Type	STORED PRESSURE N2 (NITROGEN)		STORED PRESSURE N2 (NITROGEN)		
Kapasitas	6 liter	9 liter	30 liter	50 liter	90 liter
Kelas Kebakaran	A, B		A, B		
Tabung Silinder	TANPA LAS		DENGAN LAS		
Jarak Semprot (meter)	4 s/d 8	4 s/d 8	6 s/d 9	6 s/d 9	6 s/d 9
Waktu Semprot (detik)	13	18	40	55	120
Tinggi (mm)	540	575	1050	1205	1530
Lebar (mm)	310	320	570	570	570
Diameter Tabung (mm)	160	190	370	370	370
Temperature (°C)	1 s/d 65		1 s/d 65		
Tekanan Dalam Tabung	15 bar		15 bar		
Berat Total (kg)	9.5	12.8	78	103	150
Fire Rating	3A.10B	5A.12B	10A.80B	12A.125B	30A.125B
Labeling	SCREEN PRINTING		STICKER		
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING		COLOR:RED, UV RESISTANCE POWDER COATING		

# CARBON DIOXIDE

(Carbon Dioxide (CO2))



	PORTABLE			TROLLEY		
Model	C 200 CO2	C 500 CO2	C 680 CO2	C 900 CO2	C 2300 CO2	C 4500 CO2
Type	SELF PRESSURE			SELF PRESSURE		
Kapasitas	2 kg	5 kg	6.8 kg	9 kg	23 kg	45 kg
Kelas Kebakaran	B, C			B, C		
Tabung Silinder	TANPA LAS			STEEL		
Jarak Semprot (meter)	2 s/d 7	4 s/d 12	4 s/d 12	4 s/d 14	4 s/d 14	4 s/d 14
Waktu Semprot (detik)	9	20	25	30	50	60
Tinggi (mm)	520	830	1025	1200	1500	1605
Lebar (mm)	250	382	382	462	526	576
Diameter Tabung (mm)	114	152	152	152	220	268
Temperature (°C)	-20 s/d 60			-20 s/d 60		
Tekanan Dalam Tabung	70 bar			70 bar		
Berat Total (kg)	7.7	17.5	22	30.5	95	136
Fire Rating	1B	5B	5B	6B	8B	10B
Labeling	SCREEN PRINTING			STICKER		
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING			COLOR:RED, UV RESISTANCE POWDER COATING		



# FE-36

(Clean Agent FE-36)  
Halon Replacement



## PORTABLE

Model	D 240 FE-36	D 840 FE-36	D 990 FE-36	D 1430 FE-36
Type	STORED PRESSURE N2 (NITROGEN)			
Kapasitas	2.4 lbs	6.4 lbs	9.9 lbs	14.3 lbs
Kelas Kebakaran	A, B, C			
Tabung Silinder	TANPA LAS			
Jarak Semprot (meter)	3 s/d 6	4 s/d 8	4 s/d 8	4 s/d 8
Waktu Semprot (detik)	8	10	11	13
Tinggi (mm)	300	460	455	535
Lebar (mm)	130	280	285	310
Diameter Tabung (mm)	90	130	160	160
Temperature (°C)	-20 s/d 60			
Tekanan Dalam Tabung	7 bar			
Berat Total (kg)	2.2	6.3	7.4	10
Sprinkle Detector Temperature (°C)				
Input				
Luas Proteksi				
Panjang Selang (m)				
Fire Rating	1A	1A	2A	3A.12B
Labeling	SCREEN PRINTING			
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING			

## TROLLEY

Model	D 5000 FE-36	D 10000 FE-36
Type	STORED PRESSURE N2 (NITROGEN)	
Kapasitas	50 lbs	100 lbs
Kelas Kebakaran	A, B, C	
Tabung Silinder	DENGAN LAS	
Jarak Semprot (meter)	6 s/d 12	6 s/d 12
Waktu Semprot (detik)	28	40
Tinggi (mm)	1050	1205
Lebar (mm)	570	570
Diameter Tabung (mm)	368	368
Temperature (°C)	-20 s/d 60	
Tekanan Dalam Tabung	7 bar	
Berat Total (kg)	70	100
Sprinkle Detector Temperature (°C)		
Input		
Luas Proteksi		
Panjang Selang (m)		
Fire Rating		
Labeling	STICKER	
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING	

## METRONIC

Model	SMT 1100 FE-36
Type	STORED PRESSURE N2 (NITROGEN)
Kapasitas	11 lbs
Kelas Kebakaran	A, B, C
Tabung Silinder	DENGAN LAS
Jarak Semprot (meter)	
Waktu Semprot (detik)	380
Tinggi (mm)	
Lebar (mm)	
Diameter Tabung (mm)	220
Temperature (°C)	
Tekanan Dalam Tabung	7 bar
Berat Total (kg)	8.9
Sprinkle Detector Temperature (°C)	68
Input	24 volt (DC)
Luas Proteksi	27 m <sup>3</sup>
Panjang Selang (m)	
Fire Rating	
Labeling	SCREEN PRINTING
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING



## FIRE TUBING

Model	SFT 240 FE-36	SFT 840 FE-36	SFT 990 FE-36	SFT 1430 FE-36
Type	STORED PRESSURE N2 (NITROGEN)			
Kapasitas	2.4 lbs	8.4 lbs	9.9 lbs	14.3 lbs
Kelas Kebakaran	A, B, C			
Tabung Silinder	TANPA LAS			
Jarak Semprot (meter)				
Waktu Semprot (detik)				
Tinggi (mm)	315	440	435	525
Lebar (mm)				
Diameter Tabung (mm)	90	130	160	160
Temperature (°C)				
Tekanan Dalam Tabung	7 bar			
Berat Total (kg)	2.8	7.1	8.2	10.8
Sprinkle Detector Temperature (°C)				
Input				
Luas Proteksi	1 m <sup>2</sup>	2 m <sup>2</sup>	4 m <sup>2</sup>	6 m <sup>2</sup>
Panjang Selang (m)	3 m	10 m	14 m	20 m
Fire Rating				
Labeling	SCREEN PRINTING			
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING			

## THERMATIC

Model	TND 440 FE-36	TND 1100 FE-36
Type	STORED PRESSURE N2 (NITROGEN)	
Kapasitas	4.4 lbs	11 lbs
Kelas Kebakaran	A, B, C	
Tabung Silinder	DENGAN LAS	
Jarak Semprot (meter)		
Waktu Semprot (detik)	380	380
Tinggi (mm)		
Lebar (mm)		
Diameter Tabung (mm)	220	220
Temperature (°C)		
Tekanan Dalam Tabung	7 bar	
Berat Total (kg)	5.9	8.9
Sprinkle Detector Temperature (°C)	68	68
Input		
Luas Proteksi	11 m <sup>3</sup>	27 m <sup>3</sup>
Panjang Selang (m)		
Fire Rating		
Labeling	SCREEN PRINTING	
Finishing	COLOR:RED, UV RESISTANCE POWDER COATING	

THE MOST  
ENVIRONMENTAL  
FRIENDLY  
CLEAN AGENT

ODP=0

Angka Perusak Ozon

## TECHNICAL DATA

BEST SAFE INDONESIA

Contact: (021)2938-5507 | 087-887-141-393

Email: bestsafe67@gmail.com

